

Model	Pressure		Capacity*				Motor Power	Connection Size	Dimensions (in.)			Weight	Noise
			Minimum		Maximum				Length	Width	Height	lbs	
	psi	bar	cfm	m³/min	cfm	m³/min	hp/kW						dB (A)
IMPETUS VSD 22	100	6,9	36	1,02	152,2	4,31	30/22	NPT 1 1/4"	38	43	62	1654	72
	125	8,6	35,3	1	138,1	3,91							
	150	10,3	30	0,85	122,5	3,47							
IMPETUS VSD 30	100	6,9	61,4	1,74	219,7	6,22	40/30	NPT 1 1/4"	38	43	62	1929	72
	125	8,6	55,1	1,56	203,4	5,76							
	150	10,3	52,3	1,48	180,8	5,12							
IMPETUS VSD 37	100	6,9	62,5	1,77	271,2	7,68	50/37	NPT 1 1/2"	47	49	73	2690	71
	125	8,6	57,9	1,64	241,9	6,85							
	150	10,3	60,4	1,71	213,7	6,05							
IMPETUS VSD 45	100	6,9	81,6	2,31	327	9,26	60/45	NPT 1 1/2"	47	49	73	3087	72
	125	8,6	74,9	2,12	291,3	8,25							
	150	10,3	72,7	2,06	250	7,08							
IMPETUS VSD 55	100	6,9	98,2	2,78	410	11,61	75/55	NPT 2"	55	57	77	3572	72
	125	8,6	92,2	2,61	369,4	10,46							
	150	10,3	78	2,21	323,1	9,15							
IMPETUS VSD 75	100	6,9	120,8	3,42	570,7	16,16	100/75	NPT 2"	55	57	77	4079	72
	125	8,6	120,4	3,41	511,7	14,49							
	150	10,3	119,7	3,39	12,71	448,8							

- Unit performances measured in reference conditions which are 1 bar absolute air pressure, 0% relative humidity, 20°C inlet air temperature, 71°C thermostatic valve set temperature and use of Smartoil.

- Hertz reserves its rights to make changes in its products and specifications without prior notice.

* Refers to free air delivery measured according to ISO 1217:2009, Annex E standard.

