

	Model	Pressure		Capacity		Motor HP/kW	Connection	Dimensions (in.) [Length x Width x Height]			Weight (lbs)		
		psi	bar	cfm	m³/min			Base Mounted	Tank Mounted	Tank + Dryer	Base Mounted	Tank Mounted	Tank + Dryer
SINGLE	HS1.5-S	115	8	5,65	0,16	2/1,5	1/2" NPT	29x29x35	77x34x64	74x33x64	430	996	1067
	HS2.2-S	115	8	8,48	0,24	3/2,2	1/2" NPT	29x29x35	77x34x64	74x33x64	441	1008	1078
		145	10	7,06	0,2								
	HS3.7-S	115	8	14,13	0,4	5,5/3,7	1/2" NPT	29x29x35	77x34x64	74x33x64	485	1052	1122
		145	10	12,01	0,34								
	HS5.5-S	115	8	21,19	0,6	7,5/5,5	1/2" NPT	29x29x35	77x34x64	74x33x64	507	1074	1144
		145	10	16,6	0,47								
	HS7.5-S	115	8	30,02	0,85	10/7,5	1/2" NPT	29x29x35	77x34x64	74x33x64	518	1085	1197
		145	10	24,01	0,68								
	HS7,5-D	115	8	28,25	0,8	2x(5,5/3,7)	3/4" NPT	59x32x41	76x36x70	-	893	1459	-
		145	10	24,01	0,68								
DOUBLE	HS11-D	115	8	42,38	1,2	2x(7,5/5,5)	3/4" NPT	59x32x41	76x36x70	-	937	1504	-
		145	10	33,2	0,94								
	HS15-D	115	8	60,03	1,7	2x(10/7,5)	3/4" NPT	59x32x41	76x36x70	-	970	1537	-
		145	10	48,03	1,36								
TRIPLE	HS11-T	115	8	42,38	1,2	3x(5,5 / 3,5)	1" NPT	59x32x72	-	-	1190	-	-
		145	10	36,02	1,02								
	HS16,5-T	115	8	63,57	1,8	3x(7,5/5,5)	1" NPT	59x32x72	-	-	1356	-	-
		145	10	49,79	1,41								
	HS22.5-T	115	8	90,05	2,55	3x(10/7,5)	1" NPT	59x32x72	-	-	1378	-	-
		145	10	72,04	2,04								
QUADRUPLE	HS15-Q	115	8	56,5	1,6	4x(5,5/3,7)	1" NPT	59x32x72	-	-	1422	-	-
		145	10	48,03	1,36								
	HS22-Q	115	8	84,75	2,4	4x(7,5/5,5)	1" NPT	59x32x72	-	-	1642	-	-
		145	10	66,39	1,88								
	HS30-Q	115	8	120,07	3,4	4x(10/7,5)	1" NPT	59x32x72	-	-	1664	-	-
		145	10	96,06	2,72								

- Unit performances measured in reference conditions which are 1 bar absolute air Pressure, 0% relative humidity, 20°C inlet air temperature, 71°C thermostatic valve set temperature and use of Smartoil.
- Hertz reserves its rights to make changes in its products and specifications without prior notice.